

**APPLICATION**

**FOR**

**UNITED STATES LETTERS PATENT**

**BY**

**SOLOMON S. STEINER**

**ROBERT FELDSTEIN**

**PER B. FOG**

**AND**

**TRENT POOLE**

**FOR**

**UNIT DOSE CAPSULES AND DRY POWDER INHALER**

007340-2607352



## SUMMARY OF THE INVENTION

Described is a dry powder inhaler comprising an intake section; a mixing section, and a mouthpiece. The mouthpiece is connected by a swivel joint to the mixing section, and may swivel back onto the intake section and be enclosed by a cover. The intake chamber comprises a special piston with a tapered piston rod and spring, and one or more bleed-through orifices to modulate the flow of air through the device. The intake chamber further optionally comprises a feedback module to generate a tone indicating to the user when the proper rate of airflow has been achieved. The mixing section holds a capsule with holes containing a dry powder medicament, and the cover only can open when the mouthpiece is at a certain angle to the intake section. The mixing section further opens and closes the capsule when the intake section is at a certain angle to the mouthpiece. The mixing section is a Venturi chamber configured by protrusions or spirals to impart a cyclonic flow to air passing through the mixing chamber. The mouthpiece includes a tongue depressor, and a protrusion to contact the lips of the user to tell the user that the DPI is in the correct position. An optional storage section, with a cover, holds additional capsules. The cover for the mouthpiece, and the cover for the storage section may both be transparent magnifying lenses.

The capsules may be two-part capsules where each portion has apertures which correspond to apertures in the other half when each half is partially fitted to the other half, and fully fitted to the other half. All the apertures may be closed when the two halves are rotated around their longitudinal axes with respect to each other. Each capsule may have a unique key on each half that only fits with a particular inhaler.

Therefore it is an object of the invention to provide a dry particle inhaler that can fold into a compact form.

Therefore it is an object of the invention to provide a dry particle inhaler that can be loaded with medicament easily.

# THE FUTURE OF THE FUTURE



There

to pr

Thes

### BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

Figure 1 is a schematic view of the dry particle inhaler described herein.

Figure 2 is schematic view of the mouthpiece cover.

Figure 3 is schematic view showing the angle between the intake section and the mouthpiece.

Figure 4 is a schematic view of the dry particle inhaler, showing the storage section.

Figure 5 is a schematic view of the intake section of the dry particle inhaler, showing the flow regulator and the feedback module.

Figure 6 is a schematic view of the mixing section.

Figure 7 is a schematic view of a capsule to hold medicament.

Figure 8 is a schematic view of the mouthpiece.

Figure 9 is a perspective view of a specific embodiment of the dry particle inhaler in the closed position, with a capsule inserted into the mixing section, and extra capsules stored in the storage section.

# THE BIBLE

# THE BIBLE

**THE UNIVERSITY OF CHICAGO**

**THE UNIVERSITY OF CHICAGO**

**THE UNIVERSITY OF CHICAGO**

**THE UNIVERSITY OF CHICAGO**

**THE UNIVERSITY OF CHICAGO**

**THE UNIVERSITY OF CHICAGO**

**THE UNIVERSITY OF CHICAGO**

**THE UNIVERSITY OF CHICAGO**

**THE UNIVERSITY OF CHICAGO**

**THE UNIVERSITY OF CHICAGO**

**THE UNIVERSITY OF CHICAGO**

- 80 swivel joint connecting mouthpiece and mixing section
- 90 cover for mouthpiece
- 100 protrusions on mouthpiece cover
- 110 depressions on dry particle inhaler cover to mate with protrusions on mouthpiece cover
- 120 tongue depressor on mouthpiece
- 130 protrusion on surface of mouthpiece to contact lips of device user
- 135 opening of mouthpiece to be fitted into user's mouth
- 140 intake port
- 150 flow regulator
- 160 bleed orifice
- 170 piston
- 180 piston head
- 190 piston rod
- 200 proximal portion of piston rod
- 210 distal portion of piston rod
- 220 spring
- 230 inner walls of intake section inner chamber
- 240 feedback module
- 250 mechanical fasteners in storage section
- 260 holder in mixing section for capsule
- 270 Venturi chamber
- 280 spiral shape or protrusions to impart cyclonic flow to air
- 290 cover for mixing chamber
- 291 interior of mixing section
- 292 air flow entrance to mixing section
- 294 air flow exit from mixing section
- 296 latch mechanism for mixing section cover
- 298 interior wall of mixing section
- 300 capsule

310 first tube  
 320 open end of first tube  
 330 closed end of first tube  
 340 long axis of first tube  
 350 protrusion on first tube  
 360 keying surface on first tube  
 370 secondary holes in first tube  
 372 chamfered edge of secondary hole  
 375 cone in interior of first tube  
 380 second tube  
 390 open end of second tube  
 400 closed end of second tube  
 410 long axis of second tube  
 420 protrusion on second tube  
 430 keying surface on second tube  
 440 secondary holes in second tube  
 445 cone in interior of second tube  
 450 hand of user  
 460 air flow direction  
 470 storage section  
 480 storage section cover

## DETAILED DESCRIPTION OF THE INVENTION

Figure 1 is a schematic drawing of the dry powder inhaler (10) described herein. It comprises an intake section (20), a mixing section (30) and a mouthpiece (40). An air passage (50) goes through the intake section (20), a mixing section (30) and a mouthpiece (40). A swivel joint (80) connects the mouthpiece (40) to the mixing section (30). The mixing section (20) has a cover (290) which may be a transparent magnifying lens. Arrow (460) shows the direction of air flow through the air passage (50) through the dry powder inhaler (10).





The piston (170) and spring (220) combination allow the user (not shown) to generate a vacuum in his lungs before the intake port (140) opens. Thus, by the time enough vacuum is generated to open the intake port (140), there will be sufficient air flow at a sufficient rate in the dry particle inhaler (10) to draw most of the medicament in the capsule (not shown) out of the inhaler into the proper place in the lungs of the user.

A feedback module (240) generates a signal to the user (not shown), which tells the user whether he is inspiring at the correct rate. The signal may be an audible one, in one embodiment a tone that is at a steady pitch when air flow is at a certain steady rate. In one embodiment of the dry particle inhaler (10), the signal is generated mechanically, such as be a musical reed. In another embodiment of the invention, the signal might be generated electronically, after electronic measurement of the air flow rate. The feedback module (240) would include a means for increasing or lessening the signal strength, or turning the signal off entirely. If the signal were generated by a reed, the mechanism for turning off the signal might be covering a bleed orifice which might admit the air flow generating the signal. If the signal were generated electronically, a simple push button or dial might turn on and off the signal.

Figure 6 shows a schematic of the mixing section (30) of the present invention. The mixing section has a cover (290), and a holder (260) for a medicament capsule (not shown). The holder (260) is a mechanism which grips and turns the capsule (not shown) to open and close it as the longitudinal axis (70) of the mouthpiece is rotated about the swivel joint (80) relative to the longitudinal axis (60) of the intake section. Such a mechanism may be straightforward: in a simplest embodiment, both the top and bottom halves (not shown) of the capsule could be fixed to their respective holders (260).

The Venturi chamber (270) speeds the flow of air near the capsule (not shown). Air flows in at (292), and out through (294). In one embodiment, air flows both through and around a capsule (not shown) holding a dry powder medicament. The special shape of the Venturi chamber (270),

which further includes protrusions or spiral shapes (280), imparts a cyclonic flow to the air passing through the mixing section (30). This helps to de-agglomerate particles of dry powder. The spiral shape of the interior of the mixing section (291) can be two separate spirals, in one embodiment of the invention. Mixing section (30) therefore provides the means whereby air flow is speeded up to suspend dry particles in air and de-agglomerate them, and then slow the air flow somewhat while the particles are still suspended in air. The cover (290) for the mixing section (30) may be a transparent magnifying lens, so that any writing on the capsule (not shown) may be read easily.

In one embodiment of the dry particle inhaler (10), the cover (290) of the mixing section may not be opened unless the longitudinal axis (70) of the mouthpiece forms a certain angle with the longitudinal axis (60) of the intake section, with the vertex of the angle being the swivel joint (80) connecting the mouthpiece (40) and the mixing section (30). The latch mechanism (296) for the cover (290) of the mixing section can accomplish this, by any of several mechanical means known to those of ordinary skill in the art. In the simplest embodiment, a catchment (not shown) in the cover (290) for the mixing chamber would be engaged by a slip ring (not shown) on the mixing section which was only a certain number of degrees of a circle. When the mouthpiece (40) were rotated enough relative to the intake section (20), the slip ring (not shown) would no longer engage the catchment (not shown). In one embodiment, the user could open the cover (290) when the angle were between approximately ninety and one-hundred and eighty degrees.

Figure 7 shows a medicament capsule (300) for use with an inhaler, be it a dry powder inhaler (10), or a liquid mist inhaler. The capsule (300) has two halves which fit together, here styled a first tube (310) and a second tube (380). Each tube has an open end (320, 390), and a closed end (330, 400). Each tube also has a long axis (340, 410). In addition, each tube has a number of secondary holes (370, 440). The first tube (310) fits inside the second tube (380) snugly. A protrusion (350) on the outer surface of the first



capsule, since it can be formed from a larger volume of accurately metered liquid or gel medicament. This permits very accurate microdosing. In addition, chemical reactions and drug mixtures may be made directly in the capsules described herein, then the resulting formulation dried.

In one embodiment of the capsule (300), one or more of the secondary holes (370, 440) used to admit air to the capsule is oval-shaped (elliptical). In one embodiment of the invention, the ratio of the long axis of the ellipse to the shorter axis may be between 1:1 and 3:1, and may be 2:1. This ratio may be called a vertical aspect ratio. In one embodiment of the invention, the intersection of the surface defining one or more of the secondary holes (370, 440) and the surface defining the interior of the capsule (300) meet in a chamfered, or beveled, edge. This chamfered edge creates a vortex when air flows through the secondary holes (370, 440).

Each capsule (300) also has a keying surface (or fastening mechanism) on the closed end (330) of the first tube and the closed end (400) of the second tube comprising the capsule. The keying surface (360) on the first tube may be different from the keying surface (430) on the second tube. That permits easy tactile and visual identification of the orientation of the capsule. It also permits a system where each drug formulation in a capsule (300) corresponds to a dry particle inhaler (10), so users cannot mix up drugs. In one embodiment of the invention, the keying surface (360) of the first tube mates with a keying surface (430) of a different second tube, or the mechanical fasteners (250) of the storage section (470). This permits easy storage of the capsules (300) in the storage section (470).

Figure 18 shows a medicament capsule (300), with a keying surface (360) on the first tube and a keying surface (430) on the second tube. It also shows a cutaway view of the mixing section (30) and the air flow entrance (292) to the mixing section and the air flow exit (294) to the mixing section. A spiral shape (280) is given to the interior walls (298) of the mixing section, to impart a cyclonic flow to air passing through. The air flow entrance (292) and air flow

exit (294) in this embodiment are tangential to the imaginary tube we might call the mixing section interior (291). That is to say, if a radius were drawn perpendicular to the long axis of the tube, and a tangent line were drawn to the circle perpendicular to the radius, the air flow would exit the mixing section along that tangent line. The tangential air flow exit (294) increases the velocity of the air flow, and thus helps disperse the medicament particles. As can be seen from Figure 18, the mixing section interior (291) is sized to accommodate a medicament capsule (300). Keying mechanisms (360, 430) are shaped to mate with holder (260) in the mixing section. Capsules according to the present invention may have a number of shapes, including ovoid and rectangular shapes. A variety of shapes of protrusions and slots may also be employed as keying surfaces. For instance, a keying surface might be a rectangular block, and a capsule holder might have a rectangular orifice. Alternatively, a keying surface might be triangular, hexagonal, Z-shaped, C-shaped, etc., and the holder would have the correspondingly shaped aperture.

Figure 18 also shows one embodiment of the capsule (300) where a cone (375) is located in the interior of the first tube, and a cone (445) is located in the interior of the second tube. These cones (375, 445) cause the air flow within the capsule to be cyclonic, aiding in mixing the medicament particles with the air. A cone is shown herein, but other cyclone-creating structures are contemplated by the present invention.

Figure 8 shows the mouthpiece (40) of the dry particle inhaler (10). It has a protrusion (130) on its surface to contact the lips of a user (not shown). This helps the user place the mouthpiece correctly in his mouth. The mouthpiece (40) also includes a tongue depressor (120), which may have a bulbous shape. The mouthpiece (40) is long enough that it fits approximately midway into the user's mouth (not shown). This permits greater delivery of medicament to the lungs, and less delivery to the oral cavity. The mouthpiece (40) has a particular aspect ratio of its inner channel (50) (see Figure 17). This slows the air passing through the channel so that the air borne particulates do not

end up striking the back of the user's throat. However, the air is not slowed so much that the particulates settle out of the air flow.

Figure 9, Figure 10, and Figure 11 show one specific embodiment of the dry particle inhaler (10). In Figure 9, the cover (90) of the mouthpiece is closed, and several capsule (300) are in the storage section (470). In Figure 10, the mouthpiece (40) has been rotated relative to the intake section (20). The longitudinal axis (60) [not shown] of the intake section here makes an approximately ninety degree angle with the longitudinal axis (70) of the mouthpiece section. This permits the cover (290) for the mixing section to be opened. A medicament capsule (300) taken from the storage section (470) is about to be inserted into the mixing section (30). In Figure 11, the mouthpiece (40) has been rotated to a fully extended position, the cover (290) for the mixing section has been closed, and the dry particle inhaler 910) is ready for use. In one embodiment of the dry particle inhaler (10), when the dry particle inhaler is in the closed position (Figure 9), the interior of the intake section (20) would be isolated from the outside air, but the mouthpiece (40) interior and the mixing section interior (291) would not be, permitting them to dry out after being exposed to the humid breath of a user.

Figure 12, Figure 13, Figure 14, and Figure 15 show a temporal sequence where a capsule (300) of medicament is loaded into the mixing section (30) of a dry particle inhaler (10), and the mouthpiece (40) is extended for use. The dry particle inhaler (10) described herein can also be used for nasal delivery of medicaments. A small tube (not shown) can be fitted to the end of the mouthpiece (40), and the other end of the tube inserted into the nostril. Alternatively, the mouthpiece (40) may be replaced by a nosepiece (not shown), whose free end is sized to be inserted into a nostril of a user. In another embodiment, a device such as a bellows or a syringe is used to force air through the dry particle inhaler (10) into a nosepiece inserted into the nostril of a user (not shown).

Figure 16 shows the fluid (air) flow of the dry particle inhaler (10) modeled as the equivalent electrical circuit. This is styled a “pneumatic resistance circuit”.

Figure 17 shows a schematic view of the dry particle inhaler (10). The air passage (50) through the dry particle inhaler widens as it goes through the mouthpiece (40) along the direction of the air flow (460). The opening (135) of the mouthpiece to be inserted into the mouth of the user may be roughly ellipsoid, or oval, and thus have a major axis and a minor axis. The ratio of these two may be called the horizontal aspect ratio. In one embodiment of the invention, the horizontal aspect ratio is between 2:1 and 4:1. In one embodiment of the dry particle inhaler (10), the horizontal aspect ratio is 3:1. Shaping the opening (135) in this manner keeps the drug particles collimated, maintains the optimal velocity of the particles in the air stream, and is oriented to the natural horizontal aspect ratio of the oropharyngeal region of the mouth. In one embodiment of the invention, the outline of the opening (135) resembles a bean.

The dry particle inhaler described herein may be used with medicament particles of low, medium, and high shear forces.

The dry particle inhaler and capsules described herein may be made with a variety of suitable materials known to those skilled in the art, such as metal, glass, rubber, and plastic.

While the invention has been described with reference to particular embodiments, those skilled in the art will be able to make various modifications without departing from the spirit and scope thereof.